

Paper Size	Minimum: 8.267" x 11.693" (219 mm x 297 mm) Maximum: 15.35" x 20.47" (390 mm x 520 mm)
Paper Weight	Minimum: 106 gsm/ 28lb. bond/ 6 point/ 0.0058"/ 0.15 mm Maximum: 400 gsm/ 130 lb. cover/ 18 point/ 0.015"/ 0.4 mm
	With Separator: Minimum 200 gsm
Speed	3-Step Speed Adjustment: High: 8,000 rotations - up to 4,000 sheets/hr Medium: 5,400 rotations - up to 2,700 sheets/hr Low: 2,700 rotations - up to 1,350 sheets/hr
Tolerance	±0.2 mm
Feed System	Air Suction, Top Belt Feeder
Feeder Capacity	Up to 8.7" (220 mm)
Substrates	Paper, laminates, adhesives and synthetic stocks up to 400 gsm
Power	AC 110-115V 50/60 Hz. 5 Amps
Dimensions (LxWxH)	81.10" x 27.17" x 46.85" (2,060 mm x 690 mm x 1,190 mm) with conveyor: 127" x 27.17" x 46.85" (3,226 mm x 690 mm x 1,190 mm)
Weight	882 lb. (400 kg)

Production rates are based on optimal conditions and may vary depending on stock and environmental conditions.

The leading provider of innovative precision finishing, print embellishment, and specialty finishing solutions. Contact us today to request samples or to get in touch with a finishing specialist.

Duplo USA Corporation

3050 S. Daimler St.

Santa Ana, California 92705 Toll Free: 1-800-255-1933 Telephone: 1-949-852-8222 Email: sales@duplousa.com

Find Us Online



facebook.com/duplousa

linkedin.com/company/duplo-usa-corporation




twitter.com/duplousa



youtube.com/duplousa

©2020 Duplo USA Corporation. All rights reserved. The information contained herein is subject to change without notice and products may be shown with optional features. Duplo shall not be liable for any errors or omissions contained in this document.

Duplo



UD-310 **Rotary Die Cutter**

The high-speed UD-310 Rotary Die Cutter delivers packaging and print marketing applications in distinctive shapes and sizes to help you stand out from the competition. Processing up to 4,000 sheets per hour, the UD-310 utilizes a magnetic cylinder and interchangeable flexible dies that affix to it to process paper, laminates, adhesives and synthetic stocks up to 400 qsm.

Offer custom finishing options by bringing this value-added service in-house. Suited for both long and shorter runs, the UD-310 is a highly productive and cost-efficient solution with minimal job setups and fast turnarounds.



Meet your customer's needs with flexible dies made according to their specifications. More economical and faster to manufacture, flexible dies are made of engraved magnetic steel and offer a high degree of cutting accuracy compared to steel rule and solid dies. They are easy to mount, with alignment marks on the cylinder for quick adjustments, and can be switched out in less than a minute – so you can get your jobs out the door faster.

Flexible dies can be designed to perform a range of finishing capabilities including die cutting intricate shapes, kiss cutting labels and stickers, perforations with specified teeth, and three-knife creasing to prevent toner cracking on packaging applications.



Run an efficient and productive operation with simple setups and changeovers. Once the die is mounted over the magnetic cylinder and sheets are loaded on the feed tray, job setup is made through the intuitive touchscreen panel with individual buttons to start and stop operation.

Make adjustments in 0.1mm increments along the width and length of the sheet to ensure proper sheet alignment with the fixed die position. Use the three-step speed adjustment to slow down or speed up the rotational speed of the cylinder for consistent cutting of thicker and thinner stocks.


Feeding up to 4,000 sheets per hour, the UD-310 features a high stack capacity of 8.7" (220mm) and a ultrasonic double feed sensor to detect when two or more sheets have been fed. The improved six-belt air suction feeder comes equipped with fans and air blowers to aid in the separation of double-sided laminated and synthetic stocks as well as reduces the static on digitally-printed output.




AUTOMATIC SEPARATION

With die cutting, separation is key and the UD-310 comes built-in with a revamped separation station. It automatically removes the skeleton from the finished pieces, deflecting it into the waste bin. The separation station utilizes a cassette module with deflectors and pressure rollers, and can be easily changed over to accommodate different types of jobs.

Only the finished pieces are delivered on the long conveyor stacker, which offers adjustable speeds to ensure pieces are neatly stacked for quick removal.





UD-310 Rotary Die Cutter with standard long conveyor stacker







User-friendly touchscreen panel

APPLICATIONS





Stickers and Labels



Custom-made flexible dies

Die Cut Business Cards



Door Hangers and Hang Tags



PROFITABLE, VALUE-ADDED APPLICATIONS

The UD-310 brings value, opportunity, and profitability to the business of print. Produce business cards and brochures with decorative edges, retail packages with window punches, and unique product labels for impactful presentations. Offer event invitations, flyers, and direct mailers in precise shapes that boost response rates. Create a new revenue stream by producing boxes in-house such as sleeve, tuck end, gable, pillow and so much more!



ACCURATE FINISHING

With a registration mark printed on either side of the sheet, the UD-310 ensures your jobs are finished with accuracy. The UD-310 utilizes X and Y registration sensors to read the mark and compensate for image shifting in both horizontal

and vertical directions. Process sheets face up or down, depending on the application. Registration guides adjust automatically and maintain sheet alignment throughout the job.





Scan to watch the video

- · Produces custom-shaped jobs at high speeds and faster turnarounds
- · Flexible dies designed to die cut, kiss cut, perforate, and three-knife crease
- · Automatically separates skeleton from finished pieces
- Processes paper, laminates, adhesives and synthetic stocks
- Future in-line capability with a digital press, UV coater or high pile feeder